

model type **YL-130**



- Frame / PP & Elastomer
- Lens / Polycarbonate with hard & anti-fogging coating
- Specification / Can be worn over the prescription glasses (excluding some bigger glasses)
- Size / W192 x H83 x D92
- Weight / 92g

ANSI Z136.7



Ergonomic elastomer cushion gives good fitting. Integrated spherical lens enables wide view.

NEW
model type **YL-760**



- Frame / Nylon & Elastomer
- Lens / Polycarbonate with hard coating
- Specification / Can be worn over the prescription glasses
Frame angle can be changed
Soft rubber temples(adjustable bending temples)
- Size / W160 x H58 x D170
- Weight / 147g

ANSI Z136.7



Good cushioned soft nose pads & bar Flexible temples are angle adjustable

D Laser absorption type

ORDER NAME	COLOR	Visible light transmittance(%)	Wavelength (nm)	Optical Density(OD)	FILTER CODE	CC mark
YL130 Excimer	CLEAR	○ 85%	190-380	10<	D-001	—
YL130 NdYag(SHG) CC	RED	● 16%	532	10<	D-004	D180-315 L7,R180-315 L3,DIR>315-532 L5
YL130 Alexandrite CC	PINK	● 30%	750-800-850	4-10-4<	D-006	D 180-315 L7,R 180-315 L3,DIR>315-360 L5 DI 780-860 L4,DI>860-870 L3
YL130 NdYag CC	GREEN	● 50%	1064	6<	D-009	DIR 870-925 L4,DIR>925-1065 L5 DIR>1065-1090 L3,DI 9000-11000 L3
YL130 DYE CC	BLUE	● 23%	591-598	5<	D-031	DIR 591-598 LB5 DI 5000-11000 LB3

C Laser absorption type and Application for Multi band laser

ORDER NAME	COLOR	Visible light transmittance(%)	Wavelength (nm)	Optical Density(OD)	FILTER CODE	CC mark
YL130C NdYag2 CC	AMBER	● 40%	266,355 532 1064	10< 4< 6<	C-0104	D 180-315 L7,R 180-315 L3,DIR>315-360 L5 D>360-532 L5,IR>360-532 L6, DI 800-830 L3 DI>830-925 L4,DIR>925-1065 L5 DIR>1065-1090 L3

M Type attenuation to 1/100 for alignment work

ORDER NAME	COLOR	Visible light transmittance(%)	Wavelength (nm)	Optical Density(OD)	FILTER CODE	CC mark
YL130M NdYag(SHG) CC	RED	● 30%	532	2<	M-018	D 180-315 L7,R 180-315 L3,DIR>315-360 L5 500-532 0.1W 2*10E-5J R2
YL130M Visible Laser Diode CC	BLUE	● 55%	660-680 647.1 676.4	2<	M-020	D 180-315 L7,R 180-315 L3,DIR>315-360 L5 625-640 0.01W 2*10E-6J R1 >640-655 0.1W 2*10E-5J R2 >655-665 0.01W 2*10-6J R1 >665-680 0.1W 2*10E-5J R2

D Laser absorption type

ORDER NAME	COLOR	Visible light transmittance(%)	Wavelength (nm)	Optical Density(OD)	FILTER CODE	CC mark
YL760 Alexandrite	PINK	● 30%	750-800-850	4-10-4<	D-006	—
YL760 LD-YAG	GREEN	● 35%	800-810 940,1064	7<	D-008	—
YL760 NdYag	GREEN	● 50%	1064	6<	D-009	—

C Laser absorption type and Application for Multi band laser

ORDER NAME	COLOR	Visible light transmittance(%)	Wavelength (nm)	Optical Density(OD)	FILTER CODE	CC mark
YL760C NdYag2	AMBER	● 40%	266,355 532 1064	10< 4< 6<	C-014	—

M Type attenuation to 1/100 for alignment work

ORDER NAME	COLOR	Visible light transmittance(%)	Wavelength (nm)	Optical Density(OD)	FILTER CODE	CC mark
YL760M NdYag(SHG)	RED	● 30%	532	2<	M-018	—
YL760M Visible Laser Diode	BLUE	● 55%	660-680 647.1 676.4	2<	M-020	—